



Part Number: 312XP

312XP tablet

10ZiG Wireless tablet

The 312 Mobile Tablet features the integration of a brilliant 10.4" touch display and a high performance yet energy-efficient Intel® Atom™ processor within a slim, light, and durable package. With options for a magnetic stripe reader, barcode scanner, and 3 mega-pixel camera, these tablets offer seamless information capture for instant transmission. With a touch screen, on-screen keyboards, and optional outdoor-viewable display, the 312 performs on the sales floor, in the warehouse, in the classroom, and in the field.



Benefits

<ul style="list-style-type: none"> Support for Microsoft® Windows®CE; Windows® XP Embedded; Windows® XP Professional or Linux operating system 	<ul style="list-style-type: none"> Intel® Atom™ processor; high performance with low power consumption
<ul style="list-style-type: none"> Bluetooth and Wi-Fi connection 	<ul style="list-style-type: none"> Outdoor-viewable display
<ul style="list-style-type: none"> Comprehensive remote device administration through server based Device Manager software 	<ul style="list-style-type: none"> Magnetic Stripe Reader (MSR); triple track readers (ISO TK1, 2 & 3), high-performance decoding with ultra-compact design
<ul style="list-style-type: none"> 3 Mega-pixels Camera supports auto focus, auto white balance and exposure 	<ul style="list-style-type: none"> 2D barcode scanner; reads both 1D and 2D barcodes, extremely durable, integrated for hassle-free operation



Reduce IT Costs, Increase Security and Improve Efficiency by Switching to 10ZiG Thin Clients





System	
Operating System	Windows XPe & Windows Embedded Standard (WES)
Processor	Intel Atom Z530, 1.6GHz
Browser	IE 7
Display	10.4" TFT touch display (1024 x 768)
Form Factor	ABS + PC Plastic and Magnesium-Aluminium alloy
Accessories Included	
Stylus	Yes, non-electronic tip
Protective Grips	Rubber with handstrap
Memory	
RAM	1GB DDR2 533MHz
Storage	2 GB to 16GB Internal Flash Module, 32GB to 64GB SSD
Dimensions	
Device	8.3" x 10.3" x 0.8" 210mm x 261mm x 18mm
Weight	2.05 lbs. (0.93kg)
Environmental	
Operating Temperature	0° ~ 40°C 32° ~ 104°F
Networking	
	Wi-Fi 802.11a/g/n, Bluetooth 2.0
Audio	
Control Switch & Buttons	1 Power button, 7 Front buttons
I/O Ports	1 DC-in Jack, 1 Microphone-in and 1 Headphone-out Jacks; 2 USB 2.0 ports
Speaker	1 Built in Speaker
Power	
Battery Pack	Internal (2S2P; 7.4V, 2200mAh) or (2S2P; 7.4V, 3760mAh)/ Optional: External (2S2P; 7.4V, 3760mAh)
AC/DC Adapter	Input: 100-240VAC Output: 12VDC, 3.5A
Power Cords	USA, EU, UK
Ordering Information	
PID	Description
312 XP	Embedded XP, Touch Screen, 5250, IE7, Office Viewers 2007, Shockwave, Flash, Media Player, RDP, ICA 11
8006	Ericom PowerTerm WebConnect Emulation for XPe
ACC 006 07	External Battery Pack (Li-Ion, 20W) External, Snap-on, hot-swappable battery pack, doubles the duration of mobile operation
ACC 001 05	External Battery Pack (with AC adapter and power cord) Recharges external battery offline without affecting usage of device

Accessories

Tablet Carrying case with USB keyboard Tray for vehicle mount Cradle	
Mini USB Keyboard w/Hub	
External battery charger kit	
Screen protectors for 10.4" display	
Stylus	
Desktop Charging Cradle	
Internal battery pack (Li-Ion, 14W)	
Extended Capacity Internal Battery Pack	
Automobile power adapter (12v, 3.5A, 42W) with power cord	
External Battery Pack (Li-Ion, 28AW)	
Desktop Stand	
6 Bay external battery charger	
Protective rubber grips and Shoulder Strap for tablets	
AC/DC power adapter with power cord	
Vehicle Mount Cradle - 75mm VESA	
32GB Solid State Drive (MLC SSD)	

*VT320, VT420, VT52, WYSE60, WYSE60/AIF, VAX/AIX, LINUX, IBM3151, HP70094/8, HP70092/6, HP2392A

