

Overview

The 360CE Tablet delivers the very best in mobile computing. Healthcare, manufacturing, distribution, retail, you name the industry. The 360CE Tablet is a perfect match for applications such as patient care, inventory management, shop floor, shipping, receiving, and data collection. The integration of powerful elements -- AMD LX800 processor, Microsoft's CE.Net operating system, versatile networking options, together with Citrix ICA and Microsoft RDP client/server computing protocols makes the 360CE Tablet a compelling solution for mobile computing.


Features

- 8.4" TFT Touch Screen
- Full Screen 5250/3270
- Ruggedised Industrial Strength Case
- 802.11 b/g Wireless, WEP, WPA, WPA2, 802.11x
- IE 6 for CE and Media player 9 Series for CE
- VPN Support, RDP & ICA client
- Hot Swap Batteries (up to 10 hours)
- Device support includes scanners, USB Keyboards, Bluetooth
- Various mounting options



Highlights

Unique features include customisable "Hot Spots" and full integration with 10ZiG Management Software. While "Hot Spots" enhance the use of the touch screen by triggering pre-recorded macros easing navigation through your application, integration with the 10ZiG Management Software provides centralised support and control. Terminal emulations include a Team Talk and a GUI 5250 and 3270 emulator.



Options

Part Number	360 CE
Standard RAM/Storage	256MB/64MB (RAM/Storage)
Display	8.4" TFT touch display
Operating System	Windows CE.Net
Storage	Internal flash module; CompactFlash slot or HDD; USB
Enclosure	Magnesium-Aluminum alloy
Desktop Cradle	Pass-through for Power and USB for Keyboard and Mouse
Protective Jacket	Adds drop protection
AC/DC Adapter	Input: 100-240VAC Output: 12VDC, 3.5A
Power Cords	USA, EU, UK
Battery Packs (Lithium-Ion)	Internal (14W) Optional: External (28W, 0.5lb), and Tethered Pouch (72W, 1lb)
Network Interface (incl. WLAN)	PCMCIA or mini-PCI; USB; Bluetooth Built-in; CF Slot
Wireless WAN	Integrated 802.11, Bluetooth, WEP, WPA, WPA2
Input & Control Buttons	Four (4) Front buttons; One (1) Oval 4-Way; One Power (left edge); One "Trigger" (right edge)
Input/Output Ports	12V DC-in Jack; Microphone-In; Headset; Jack; USB Port 2.0
Dimensions	7.9 x 9.6 x 0.8 (in) 200 x 240 x 18 (mm)
Base Weight	1.9 lbs (0.86 kg)
Operating Temp.	0° – 40°C

Ordering Information

PID	Description
360CE	CE.Net, Touch Screen, 5250/3270, IE6, Media Player, VPN support, RDP, ICA
ACC-006-07	External Battery Pack (Li-Ion, 20W) External, snap-on, hot-swappable battery pack – doubles the duration of mobile operation
ACC-001-05	External Battery Charger Kit (with AC adapter and power cord) Recharges external battery pack offline without affecting usage of device

Accessories


Carrying case with USB




Vehicle mount cradle



External battery pack



External battery charger kit



Screen protectors for 8.4" display



Stylus



VESA mount cradle assembly



Enhanced cradle assembly



Protective rubber bumper with handstrap



Internal battery pack



Automobile power adapter



AC/DC power adapter with power cord



Desktop Stand



USB - Ethernet Dongle



6-Bay External Battery Charger

