

Overview

The 360XP Tablet delivers the very best in mobile computing. Healthcare, manufacturing, distribution, retail, you name the industry. The 360XP Tablet is a perfect match for applications such as patient care, inventory management, shop floor, shipping, receiving, and data collection. The integration of powerful elements -- AMD LX800 processor, Microsoft's XP-embedded operating system, versatile networking options, together with Citrix ICA 10 and Microsoft RDP 6 client/server computing protocols makes the 360XP Tablet a compelling solution for mobile computing.



Features

- 8.4" TFT Touch Screen
- Full Screen 5250/3270
- Ruggedised Industrial Strength Case
- Built in Authentic biometric sensor compatible with Valid Technologies
- 802.11 b/g Wireless, WEP, WPA, WPA2, LEAP, PEAP, 802.11x, 802.11n* (*optional)
- Available PCMCIA slot can be used with Verizon, Sprint, AT&T, etc.
- IE 7 SP2 – MS JVM, Sun Java, Shockwave, Flash, and Media player 11
- Adobe 8.10 and Office Viewers
- Hot Swap Batteries (up to 10 hours)
- Device support includes scanners, USB Keyboards, Bluetooth
- Various mounting options



Highlights

Unique features include customisable "Hot Spots" and full integration with 10ZiG Management Software. While "Hot Spots" enhance the use of the touch screen by triggering pre-recorded macros easing navigation through your application, integration with the 10ZiG Remote Manager provides centralised support and control. Terminal Emulations include 10ZiG Secure GUI (5250) and Ericom Powerterm (3270, VT100, ...) by request.



Options

Part Number	360 XP
Standard RAM/Storage	512MB/1GB(RAM/Storage)
Display	8.4" TFT touch display
Operating System	Windows XP Embedded SP2
Storage	Internal flash module; CompactFlash slot or HDD; USB
Enclosure	Magnesium-Aluminum alloy
Desktop Cradle	Pass-through for Power and USB for Keyboard and Mouse
Protective Jacket	Adds drop protection
AC/DC Adapter	Input: 100-240VAC Output: 12VDC, 3.5A
Power Cords	USA, EU, UK
Battery Packs (Lithium-Ion)	Internal (14W) Optional: External (28W, 0.5lb), and Tethered Pouch (72W, 1lb)
Network Interface (incl. WLAN)	PCMCIA or mini-PCI; USB; Bluetooth Built-in; CF Slot
Wireless WAN	Integrated 802.11, Bluetooth, WEP, WPA, WPA2, LEAP, PEAP
Input & Control Buttons	Four (4) Front buttons; One (1) Oval 4-Way; One Power (left edge); One "Trigger" (right edge)
Input/Output Ports	12V DC-in Jack; Microphone-In; Headset; Jack; USB Port 2.0
Dimensions	7.9 x 9.6 x 0.8 (in) 200 x 240 x 18 (mm)
Base Weight	1.9 lbs (0.86 kg)
Operating Temp.	0° – 40°C

Ordering Information

PID	Description
360XP	Embedded XP, Touch Screen, 5250, IE7, Office Viewers, Shockwave, Flash, Media Player, RDP, ICA
8006	Ericom Emulation for XPe
ACC-006-07	External Battery Pack (Li-Ion, 20W) External, snap-on, hot-swappable battery pack – doubles the duration of mobile operation
ACC-001-05	External Battery Charger Kit (with AC adapter and power cord) Recharges external battery pack offline without affecting usage of device

Accessories


Carrying case with USB keyboard kit




Vehicle mount cradle



External battery pack



External battery charger kit




Screen protectors for 8.4" display



Stylus



VESA mount cradle assembly



Enhanced cradle assembly



Protective rubber bumper with handstrap



Internal battery pack



Automobile power adapter



AC/DC power adapter with power cord



Desktop Stand



USB - Ethernet Dongle



6-Bay External Battery Charger

