

Overview

The 410XP Tablet delivers the very best in mobile computing. Healthcare, manufacturing, distribution, retail, you name the industry. The 410XP Tablet is a perfect match for applications such as patient care, inventory management, shop floor, shipping, receiving, and data collection. The integration of powerful elements -- AMD Geode LX800 processor, Microsoft's XP-embedded operating system, versatile networking options, together with Citrix ICA and Microsoft RDP client/server computing protocols makes the 410XP Tablet a compelling solution for mobile computing.



Features

- 10.4" TFT Touch Screen
- Full Screen 5250 (and other optional Ericom emulations)
- IP53 compliant
- 3.5 hour battery life
- Multiple 2.5ft drop tested
- Built-in stand
- Sunlight readable solution for outdoor applications optional
- Built-in 802.11 a/b/g Wireless
- Rich I/O port array for application expansion
- IE 7 – MS JVM, Sun Java, Shockwave, Flash, and Media player 11
- Adobe 8.10 and Office Viewers 2003



Water
IPX3



Dust
IPX5



Free Drop
70cm



Operating
Temperature
0°C to +40°C



Fanless

Options

Part Number	410 XP
Standard/Maximum RAM	512MB/2GB
Display	10.4" TFT touch display (1024 x 768)
Operating System	Windows XP Embedded
Storage	2GB Compact Flash card 1.8" HDD 30GB optional
Ruggability Rating	IP53, multiple 2.5 ft drop
AC/DC Adapter	Input: 50-60Hz Output: 19V, 3.16A Universal AC 100V-240V, 60W
Power Cords	UK, EU, USA
Battery Packs (Lithium-Ion)	Rechargeable Li-ion smart battery 14.8V, 2200mAH, 3.5 hour battery life
Wireless WAN	Integrated 802.11 a/b/g
Input & Control Buttons	Five software programmable buttons, one navigation button with an enter function
Input/Output Ports	RS-232 port; Two USB Type A connectors; SD slot, RJ45 LAN port, Audio for headphone/microphone, VGA out connector, DC-in jack, Docking connector for cradle
Dimensions	10 x 9.4 x 1.2 (in) 295 x 238 x 30 (mm)
Base Weight	3.5 lbs (1.6 kg)
Operating Temp.	0° – 40°C

Accessories



Built-in stand



VESA mount



Docking cradle

Ordering Information

PID	Description
410XP	Embedded XP, Touch Screen, 5250, IE7, Office Viewers, Shockwave, Flash, Media Player, RDP, ICA
8027	1GB RAM
410-01	VESA mount (Factory option)
410-02	Sunlight readable screen (Factory option)
410-03	Docking cradle

