



Part Number: 6602

LTC 6000 thin client

Enterprise Class Thin Client

The LTC 6000 offers a combination of high performance and expandability. Powered by a 1.6GHz VIA Eden ULV processor, this unit is powerful, energy efficient and secure.

Designed for easy expansion and capable of rich multi media graphics, the LTC 6000 provides a superior end user experience.

The LTC 6000 supports three modes of operation:

Desktop Mode	Windows Vista type user interface provides access to all applications in a windowing environment.
WBT Mode	Windows based Terminal mode, where the terminal behaves like a CE.NET device with full screen applications, GUI 5250/3270, Terminal Server access, Citrix or VDI which auto start and auto reconnect.
Kiosk Mode	Dedicated Kiosk type of interface not configurable by the user of the terminal



**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**

✓ Linux Operating System	✓ Centralised Management
✓ No Moving Parts	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 Personal/Enterprise
✓ Read Only File System	✓ Wide Screen Support
✓ Embedded Firefox Browser	✓ 1600 X1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built in Kensington Security Lock
✓ Energy Efficient	✓ RoHS Compliant
✓ TN5250e/TN3270e with Split Screen	✓ Dual Monitor Support
✓ Open Office & Skype Capabilities	✓ Cisco VPN





System	
Operating System	Linux 2.6 Kernel
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA Eden ULV 1.6 GHz
Browser	Firefox 3.0
Video Resolution	Up to 1600 x 1200 x 32 bit color
Wide Screen Support	•
Memory	
RAM (Stand/MAX)	512MB/2GB
Storage (Stand/MAX)	512MB/16GB
Software Configuration	
Host Access	Supports TN5250e, TN3270e, PuTTY with optional Ericom Power Term.
ICA	Version 11 with HDX
RDesktop	1.6
Client Software	Adobe Acrobat Reader Adobe Flash Player 10 Sun JVM 1.6 VNC Shadowing Cisco VPN Thunderbird Email Linux PN Agent NX Client X Window Skype Open Office
VDI Clients:	Quest vWorkspace V6.2, Leostream, Ericom PowerTerm WebConnect, VMware View 4 with PCoIP and 2X VirtualDesktopServer
Dimensions	
Device	22" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm
Weight	3.7 lbs. (1.7kg)
Audio	
Mic In/Line Out	•
Speaker	x 1 (built in 1W internal Speaker)
Management	
10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Configuration of Various Connection Types including 5250	•
Update of Firmware	•

Ports	
USB Ports Type 2	4
PS2 Port	Keyboard and mouse via Y cable
Serial Port (D Sub, 9 Pin Male Connector)	2 *
Parallel Port	1 *
Environmental	
Operating Temperature	0° ~ 40°C 32° ~ 104°F
Operating Humidity	20% ~ 90% non condensing
Power	
Consumption	14 watts average
AC/DC Adapter	Included
Networking	
	Autosensing, 10/100/1000 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option.
Compliance	
	RoHS WEEE CE FCC
Features	
Security Features	Kensington Security Lock Slot Auto start/auto restart connection, Lock down user interface
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information	
PID	Description
6602	LTC 6000, Linux, Open Office, Skype, RDP, ICA, TN5250e, TN3270e and Optical Mouse
9011	PCI Expansion Card (Serial and Parallel port)
9009	Internal Wireless (b/g)
9010	Internal Wireless (b/g/n)
8122x	122 Key Driverless PC Keyboard
8104b	104 Key PC Keyboard

* One parallel and one serial port available with optional PCI card (9011)

