



Part Number: 5466

RBT 466 thin client

Value Class Thin Client

The RBT 466 is an affordable, energy efficient, compact thin client. This unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The RBT 466 has no moving parts and consumes only 8.9 watts of energy.



The RBT 466 supports three modes of operation:

WBT Mode	Windows based Terminal mode, where the terminal behaves like a CE.NET device with full screen applications, GUI 5250/3270, Terminal Server access, Citrix or VDI which auto start and auto reconnect.
Desktop Mode	Windows Vista type user interface provides access to all applications in a windowing environment.
Kiosk Mode	Dedicated Kiosk type of interface not configurable by the user of the terminal

**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**

✓ Linux Operating System	✓ Centralised Management
✓ Small Form Factor for Space Saving	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 Personal/Enterprise
✓ Read Only File System	✓ Wide Screen Support
✓ Embedded Firefox Browser	✓ 1600 X1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built in Kensington Security Lock
✓ Energy Efficient (Only 8.9W)	✓ RoHS Compliant
✓ TN5250e/TN3270e with Split Screen	✓ Energy Star Compliant
✓ VESA Mounting Capability	✓ Cisco VPN





System

Operating System	Linux 2.6 Kernel
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA Eden 400MHz
Browser	Firefox 3.0
Video Resolution	Up to 1600 x 1200 x 32 bit color
Wide Screen Support	•

Memory

RAM (Stand/MAX)	256MB/1GB
Storage (Stand/MAX)	512MB/512MB

Software Configuration

Host Access	Supports TN5250e, TN3270e, PuTTY with optional Ericom Power Term.
ICA	Version 11 with HDX
RDesktop	1.5
Client Software	Adobe Acrobat Reader Adobe Flash Player 10 Sun JVM 1.6 VNC Shadowing Cisco VPN Thunderbird Email Linux PN Agent NX Client X Windows
VDI Clients:	Quest vWorkspace V6.2, Leostream, Ericom PowerTerm WebConnect, VMware View 4 with PCoIP and 2X VirtualDesktopServer

Dimensions

Device	14" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm
Weight	1.7 lbs. (0.75kg)

Audio

Mic In/Line Out	•
Speaker	x 1 (built in 1W internal Speaker)

Management

10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Configuration of Various Connection Types including 5250	•
Update of Firmware	•

Ports

USB Ports Type 2	x4
PS2 Port	•

Environmental

Operating Temperature	0° ~ 35°C 32° ~ 95°F
Operating Humidity	20% ~ 80% non condensing

Power

Consumption	8 9 watts average
AC/DC Adapter	Included

Networking

	Autosensing, 10/100 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option
--	---

Compliance

	RoHS
	WEEE
	CE
	FCC
	Energy Star Compliant

Features

Security Features	Kensington Security Lock Slot Auto start/auto restart connection, Lock down user interface
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information

PID	Description
5466	RBT 466, Linux, VDI Clients, RDP, ICA, TN5250e and TN3270e
MS001	Optical Mouse
9001	USB to Centronics
9004	VESA Mounting Bracket (with short VGA cable)
9009	Internal Wireless (b/g)
9010	Internal Wireless (b/g/n)
8009	OpenOffice Suite and Java Cache
8122b	122 Key Driverless PC Keyboard
8104b	104 Key PC Keyboard

