

RBT-472v Thin Client

The RBT-472v Thin Client is designed for a desktop virtualisation (VDI) environment. Complete with VMware View, Citrix XenDesktop, 2X VirtualDesktopServer, Quest vWorkspace, Leostream Connection Broker and Ericom PowerTerm Web Connect, this unit offers increased flexibility and a complete desktop experience.

The RBT-472v delivers on the promise of increased performance and low cost in a compact package. This unit weighs just over 1lb. allowing flexible mounting options and lower shipping costs. The VIA Eden 400MHz processor provides users with exceptional performance and low power consumption.



Versatile Operating Environment

The RBT-472v supports two modes of operation:

WBT Mode - Windows based Terminal mode has just a connection manager. WBT mode thin client auto starts and auto connects so users can boot direct into their virtual PC desktop. The auto reconnect feature provides users reconnect the virtual desktop in the event of a disconnection.

Kiosk Mode - Ideal for XenDesktop users or other browser interfaces, where the interface is lock-down and the user can not change the browser settings.



*Mounted on the back of 17" monitor

Benefits:

- Industry standard OS (Linux 2.6 Kernel)
- Small form factor for space-saving, desktop and mounted deployments
- Designed for a virtual desktop deployment
 - VDI clients include VMware View, XenDesktop, 2X VirtualDesktopServer, Quest vWorkspace, Leostream Connection Broker, and Ericom WebConnect
- Internal 802.11 b/g/n wireless option with WEP, WPA, WPA2 Personal/Enterprise
- Includes RDP, ICA and Proprietary clients
- Firefox 3.0 browser with JVM and Flash Player 10
- Cisco VPN Client provides remote users automatic access to their virtual PC desktop



RBT-472v Thin Client

System	
Operating System	Linux 2.6 kernel
Form Factor	Compact stand-alone metal case
Management	10ZiG Management Software
Processor	VIA Eden 400MHz
Browser	Firefox 3.0
Video Res.	Up to 1920 x 1440 (Supports Wide Screen)
Memory	
RAM (Stand/MAX)	256MB/1GB
Storage (Stand/MAX)	256MB/1GB
Software Configuration	
ICA	Version 11 with HDX
RDesktop	1.5
Client Software	VNC Shadowing
	Sun JVM 1.6
	Flash Player 10
	Quest vWorkspace V6.1
	Leostream
	Citrix XenDesktop
	Ericom PowerTerm WebConnect
	VMware View
	2X VirtualDesktopServer
	Linux PN Agent
	Secure Gateway
	PDF Viewer
	Thunderbird
	NX Client
	X-Windows
	Cisco VPN
Dimensions	
Device	1.4" W x 5.9" H x 4.7" L 35mm x 150 mm x 120 mm
Weight	1.4 lbs. (0.6kg)
Audio	
Mic In/Line Out	●
Speaker	x 1 (built-in 1W internalSpeaker)
Ports	
USB Ports - Type 2	x4
PS2 Port	●
Environmental	
Operating Temperature	0° ~ 35°C 32° ~ 95°F
Operating Humidity	0% ~ 90% non-condensing
Power	
Consumption	8 - 9 watts average
AC/DC Adapter	DC 12V/2A Included

Networking	
	Autosensing, 10/100 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option

Management	
10ZiG Remote Manager	●
Various client configurations	●
Shadow terminals	●
Status indication	●
Power on, Log off, Reboot and Shut down	●
Task Scheduler	●
Cloning of Terminals	●
Group Operations	●
Configuration of Various connection types including 5250	●
Update of Firmware	●

Compliance	
	RoHS
	WEEE
	CE
	FCC
	Energy Star Compliant

Features	
Security Features	Kensington Security Lock Slot
	Administrative and user passwords
	Lock-down user interface
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information	
PID	Description
5472v	VDI Software Image
9001	USB to Centronics Parallel
9004	VESA Mounting Bracket (Includes Short VGA Cable)
9009	Internal Wireless (b/g)
9010	Internal Wireless (b/g/n)
8104b	104-Key PC Keyboard

